





## RAVENOL LGC Premix -40°C Protect C13



ART.-NR. 1410129

1,5 L | 1410129-150 5 L | 1410129-005 10 L | 1410129-010 20 L | 1410129-020 20 L | 1410129-B20 1000 L | 1410129-700 APPROVALS VW TL 774-J (FÜR KONZENTRAT)
RECOMMENDATIONS VOLKSWAGEN VW G013A8JM1, G013A8JM8,
G013A8JM9 | AUDI, SKODA & SEAT

**RAVENOL LGC Premix -40°C Protect C13** is an eco-friendly 1.2- Ethanediol (monoethylene glycol) based coolant with 20% glycerine additive for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated on a proven inhibitor development by combining glycerine and silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL LGC Premix -40°C Protect C13** protects the cooling system from rust, frost, and in summer, from overheating.

## **Application Notes**

**RAVENOL LGC Premix -40°C Protect C13** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

<u>Instructions:</u> Add **RAVENOL LGC Premix -40°C Protect C13** to radiator to fill line.

## Characteristics

RAVENOL LGC Premix -40°C Protect C13 offers:

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- · Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

## - Certificate / Product Information -







Property	Unit	Data	Audit
Density at 20°C	kg/m³	1080	EN ISO 12185
Colour		violett / lila	visual
pH- value		7,8	ASTM D 1287
Freezing point	°C	-40	ASTM D 1177

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 13. January 2020