

# Alycol Cool Ready -35

## coolant, ready to use



Alycol Cool Ready -35 is a pink coloured ready to use monoethylene-glycol based coolant liquid, containing a corrosion inhibitor additive. It is free from nitrites, amines, borates, silicates and phosphates, and is suitable for filling the cooling systems of internal combustion engines. Alycol Cool Ready -35 can be mixed with other monoethylene-glycol and monopropylene-glycol based antifreeze coolants without limitation.

### Application



Cooling systems of passenger and commercial vehicles, agricultural and construction machines

Cooling systems containing cast iron, aluminium and copper parts

### Features and benefits

Good corrosion protection

Forms a stable protective film on the inner surface of the cooling system to ensure a long lifetime

Application specific composition

Protection against cavitation and sludge sedimentation

Compatible with construction materials

There's no damage to the plastic and rubber parts of the cooling system

### Specifications and approvals

BS 6580:2010  
ASTM D 3306

### Properties

Properties	Typical values
Appearance	pink
Density at 15°C [g/cm <sup>3</sup> ]	1,069
pH value	7,9
Freezing point [°C]	-36
Alkalinity [ml 0,1M HCl/10 ml]	1,4
Refractive index at 20 °C	1,384
Content of chlorid [mg/kg]	<10
Content of sulphate [mg/kg]	<10

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Should be stored in its original packaging with airproof sealing, separately from foods, in a place protected against water and sunshine, locked away from children.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: -35°C - +30°C

# Alycol Cool Ready -35

coolant, ready to use



## Ordering information

Custom Tariff Number 38200000

### SAP code and packaging:

19002812	Alycol Cool Ready -35 1L	1 l plastic bottle
19002813	Alycol Cool Ready -35 4L	4 l plastic can
19002815	Alycol Cool Ready -35 220KG	216.5 l steel drum (for order only)

### Order booking:

Please contact your local distributor or sales partner for ordering details.