

# MOL Standard S 50

## monograde diesel motor oil



MOL Standard Diesel 50 is a monograde seasonal diesel engine oil produced from mineral base oils, containing additives that modify the flow characteristics and ensuring appropriate performance levels, for use in older naturally aspirated diesel engines.

### Application



Low- and medium-duty trucks, buses, agricultural and road construction machines, which do not have a turbocharger

Naturally aspirated diesel engines of older construction

### Features and benefits

High operational viscosity

Reduces oil consumption and improves internal sealing of the engine

Good lubricating film strength

Stable load-carrying lubricating film even in heavily worn, older engines

### Specifications and approvals

Viscosity grade: SAE 50

API CC

MIL-L-2104B

### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,899
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	272,7
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	20,6
Viscosity index	88
Pour point [°C]	-15
Flash point (Cleveland) [°C]	250
Base number (BN) [mg KOH/g]	3,5

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

# MOL Standard S 50

## monograde diesel motor oil



### Ordering information

Custom Tariff Number 27101981

#### SAP code and packaging:

13006538 MOL Standard S 50 10LA  
13006539 MOL Standard S 50 180KG

10 l plastic can  
216.5 l steel drum (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.