



## RAVENOL ODL 32 Druckluftoel



ART.-NR. 1323404

1 L | 1323404-001  
10 L | 1323404-010  
20 L | 1323404-020  
20 L | 1323404-B20  
1000 L | 1323404-700

**FABRICATION MINERAL**

**RECOMMENDATIONS** ATLAS COPCO | FESTO | HILTI | BOSCH | MAKITA | BLACK&DECKER | CRESS | RYOBI | DEWALT | SUMAKE | SENO | HITACHI

**RAVENOL ODL 32 Druckluftoel** is a special-compressed-air-oil for pneumatic tools of all systems.

**RAVENOL ODL 32 Druckluftoel** bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.

## Application Notes

**RAVENOL ODL 32 Druckluftoel** is specially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe. Mind the manufacturer's instructions.

## Characteristics

**RAVENOL ODL 32** offers:

- a high performance level
- a very good viscosity temperature behaviour
- a good adherence
- a high aging resistance
- a reliable wear protection
- an excellent corrosion protection
- neutrality of sealing materials

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	867,7	EN ISO 12185
Colour		hellgelb	visual



Property	Unit	Data	Audit
Viscosity at 100°C	mm <sup>2</sup> /s	5,4	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	32,1	DIN 51 562
Viscosity index VI		102	DIN ISO 2909
Pourpoint	°C	-30	DIN ISO 3016
Flash point (COC)	°C	224	DIN ISO 2592
FZG-Test A/8,3/90 damage loading step		12	DIN 51 354

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 18. January 2021