

Fully Synthetic

Kixx ATF DX-VI

Top Performance Low Viscosity Automatic Transmission Fluid

GM DEXRON®-VI, FORD MERCON LV, JASO 1A-LV



DESCRIPTION

Kixx ATF DX-VI is a premium performance, low viscosity multi-vehicle fluid for modern automatic transmissions, which is blended with synthetic base stocks and advanced high performance additives. It is specially designed to provide improved fuel efficiency and excellent shudder control performance. Kixx ATF DX-VI is officially approved for use by GM and meets or exceeds the requirements of latest OEM specifications such as Ford MERCON LV, Toyota WS, Nissan Matic S, Hyundai SP-IV/SP-IV-RR. It is also suitable for most modern 6+ speed automatic transmissions.

PERFORMANCE STANDARDS

Auto Maker	Specification	Auto Maker	Specification
GM	DEXRON® VI Approved DEXRON® III G, IIIH DEXRON® II, IID, IIE	Mercedes / Daimler	MB 236.10/11/12/14/15 MB 226.41/6/7/8/9
		Suzuki	3314, 3317
Toyota / Lexus	Type D-III Type T, T-III, T-IV Type WS (JWS 3324)	Volvo	P/N 1161521, 1161540, 1161640
		Ford / Lincoln	WSS M2C 922A1 WSS M2C 924A
VW / Audi	G 052 533/055 G 052 025 (A2) G 052 990 (A2) G 055 025 (A2) G 055 540 (A2) G 060 162 (A1, A2, A6)	Honda	ATF-Z1(except in CVTs) ATF Type 3,0/3,1
		Mazda	JWS 3317, Type T-IV D-II, M-III, M-V, FZ, F-1
		Hyundai / Kia	SP-III, SP-IV, SP-IV RR ATF Red-1K JWS 3309 T-4 NWS 9638 T-5
		Mitsubishi	Diaqueen SK, AW, SP-IV Diaqueen J2, J3 Diaqueen ATF-PA
ZF	Lifeguardfluid 6, 8, 9	Nissan	Matic-D, Matic-J, Matic-K Matic-S, Matic-W
BMW	ATF-3+ JWS 3309 (T-IV) LA2634, LT1141 7045E, ETL-8072B 83 22 0 142 516 83 22 2 152 426 83 22 2 305 397	JASO	M315-2013 1A-LV, Class 1A



CUSTOMER BENEFITS

- OEM approved and licensed by GM(DEXRON®-VI).
- Improved fuel efficiency and shudder control performance.
- Excellent transmission cleanliness and durability by oxidation/thermal stability.
- Good start operation in cold climates thanks to its excellent low-temperature fluidity.
- Excellent friction performance and shift feel durability for comfort transmission shift.
- Exceptional wear and corrosion performance for long equipment life.

KEY PROPERTIES

Density, kg/L @15°C	0.864
Kinematic Viscosity, mm ² /s @ 40°C	30.3
Kinematic Viscosity, mm ² /s @ 100°C	6.0
Pour Point °C	-52
Flash Point °C	224
Brookfield Viscosity, cP @-20°C	864
Brookfield Viscosity, cP @-40°C	12,100
Package (Liters)	1, 4T, 200

UNIQUE FEATURES



- At least 20% longer than Competitor
- At least 30% longer than Toyota T-III
- Kixx ATF DX-VI consistently within JASO limit