

PerFluid® GM

Product Overview

PerFluid® GM is a Food Safe H1 registered high temperature graphite chain lubricant designed for the use on Tunnel and Stone bake oven chains at temperatures up to 400°C.

The product can be applied manually but is best applied automatically via the PFL automatic lubrication system which can ensure the current draw remains low and constant.



Features and Benefits

- Unique Polyglycol fortified with food grade graphite
- Very low fume
- Can be applied during production to hot chains
- Water Soluble making it user friendly
- High stable dispersion
- Audit compliant H1 Registered
- Halal Certified
- Kosher Certified
- OEM Approved

It has been successfully proven since 2005 at major bakeries Worldwide and is approved by Spooner Industries & AMF

Applications

PerFluid® GM is particularly suited for the lubrication of:

- High temperature tunnel oven chains

Available Pack Sizes

Pack Size	Product Code
5kg	FG40003
20kg	FG40377
190kg	FG40270



Typical Properties

Appearance	Black Liquid
Kinematic Viscosity @ 40°C , cSt (ASTM4451)	220
Kinematic Viscosity @ 100°C , cSt (ASTM4451)	25
Operating Range (°C)	0 – 230 (>260 as a dry lubricant)
Shell 4 ball – Weld Load	500kg
Specific Gravity @ 20°C	1.06

Health and Safety

To obtain Material Safety Data Sheet (MSDS),
contact our technical team

This information is given in good faith but without warranty as the use of the product is outside
the control of Performance Fluids Ltd

Revision SB210222

Performance Fluids Ltd

T: +44(0) 1282 878240

E: sales@performancefluids.co.uk

W: www.performancefluids.co.uk



Certificate Number: 4769-QMS-001
ISO 9001:2015
Certificate Number: 4769-EMS-001
ISO 14001:2015
Certificate Number: 4769-HSI-001
ISO 45001:2018 SSIP



Innovators in Lubrication Design