


# MOL Hidrofluid A

## automatic transmission fluid



MOL Hidrofluid A is an automatic transmission fluid produced from highly refined base oils, containing additives corresponding to the load. Based on technical experience the product is suitable for use in applications where GM Type A Suffix A performance level is prescribed.

### Application



Hydrodynamic clutches  
Gear drives, torque converters and hydraulic systems  
Hydraulic servo equipment

### Features and benefits

|                                      |   |
|--------------------------------------|---|
| Good wear protection                 | Reliable equipment protection and long machine lifetime           |
| Good thermal and oxidation stability | No harmful deposits are formed even at high temperatures          |
| Excellent corrosion protection       | Extreme long term protection of steel and non-ferrous metal parts |
| Low foaming tendency                 | Stable, continuous lubricating film, giving reduced wear          |

### Properties

| Properties   | Typical values |
|--|----------------|
| Density at 15°C [g/cm <sup>3</sup> ]               | 0,875          |
| Kinematic viscosity at 40°C [mm <sup>2</sup> /s]   | 47,1           |
| Kinematic viscosity at 100 °C [mm <sup>2</sup> /s] | 7,4            |
| Viscosity index                                    | 120            |
| Pour point [°C]                                    | -30            |
| Flash point (Cleveland) [°C]                       | 200            |

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.  
During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.  
For further details please read the Material Safety Data Sheet of the product.  
Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.  
In the original container under the recommended storage conditions: 60 months  
Recommended storage temperature: max. 40°C

# MOL Hidrofluid A

## automatic transmission fluid



### Ordering information

Custom Tariff Number 27101987

#### SAP code and packaging:

13006272 MOL Hidrofluid A 10LA

13006274 MOL Hidrofluid A 50KG

13006273 MOL Hidrofluid A 180KG

10 l plastic can

60 l steel drum

216.5 l steel drum

#### Order booking:

Please contact your local distributor or sales partner for ordering details.