



RAVENOL Petrol Performance Optimizer Premium



ART.-NR. 1390201

300 ml | 1390201-300

RECOMMENDATIONS LEICHT MISCHBARES BENZIN-ADDITIV | DIE WIRKSAMKEIT DER NOX REDUKTION IST DURCH DEN TÜV-THÜRINGEN GEPRÜFT UND ZERTIFIZIERT.

RAVENOL Petrol Performance Optimizer Premium is a premium fuel additive for all petrol engines for cleaning all components in contact with fuel. Ensures a technically safe and economic operation.

RAVENOL Petrol Performance Optimizer Premium provides a verifiable saving of fuel, a higher octane rating and increased performance.

RAVENOL Petrol Performance Optimizer Premium reduces NOx emissions, which is tested and certified by the TÜV (Technical Inspection Agency) Nord.

RAVENOL Petrol Performance Optimizer Premium guarantees ideal combustion. This prevents deposits and oxidation by-products on fuel lines, injection needles, cylinders, spark plugs and combustion chamber.

RAVENOL Petrol Performance Optimizer Premium prolongs the service life of catalytic converters and lambda probes by means of optimum combustion.

Application Notes

RAVENOL Petrol Performance Optimizer Premium is added to the petrol.

Area of application:

- Petrol-operated engines
- Can be used preventively at every service
- In the event of increased fuel consumption
- In cases where inadequate fuel is suspected
- When using E10 petrol blend
- Also recommended for direct injection engines

Application: Pour the contents of the container into the tank. Fuel volume up to 60 l of petrol. Minimum fuel capacity according to volume of fuel reserve.



Characteristics

RAVENOL Petrol Performance Optimizer Premium offers:

- Certified efficacy of the NOx reduction by the TÜV (Technical Inspection Agency) Thuringia
- guarantees optimum combustion
- Saving of fuel
- Cleaning of fuel lines, injection needles, cylinders, spark plugs and combustion chamber. Increases octane rating and performance.
- Prolongs the service life of catalytic converters and lambda probes

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	790	EN ISO 12185
Colour		gelb	visual
Viscosity at 40°C	mm ² /s	7	DIN EN ISO 3104
Flash Point PM	°C	15	DIN ISO 3679

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 10. December 2020