



## RAVENOL Getriebeoel LS SAE 75W-90



**VISCOSITY** 75W-90

**SPECIFICATIONS** API GL-5 | MIL-L-2105 D | API GL-5 + LS (LIMITED SLIP)

**FABRICATION** SYNTHETIC

**RECOMMENDATIONS** ZF TE-ML 05C/D | GM 1940058 | GM 93165388 | GM 88862624 | GM 88862625

**RAVENOL Getriebeoel LS SAE 75W-90** is a semi-synthetic lubricant for mechanical transmissions.

**RAVENOL Getriebeoel LS SAE 75W-90** is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

### ART.-NR. 1222102

1 L	1222102-001
4 L	1222102-004
10 L	1222102-010
20 L	1222102-020
20 L	1222102-B20
60 L	1222102-060
60 L	1222102-D60
208 L	1222102-208
208 L	1222102-D28
1000 L	1222102-700

## Application Notes

**RAVENOL Getriebeoel LS SAE 75W-90** was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

## Characteristics

**RAVENOL LS SAE 75W-90** offers:

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	870,0	EN ISO 12185
Colour		gelb	visual
Viscosity at 100°C	mm <sup>2</sup> /s	17,1	DIN 51562-10
Viscosity at 40°C	mm <sup>2</sup> /s	118,3	DIN 51562-10
Viscosity index VI		158	DIN ISO 2909
Brookfield Viscosity	mPa*s	88.800	ASTM D 2983
Pourpoint	°C	-42	DIN ISO 3016
Flash point	°C	192	DIN ISO 2592
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 04. May 2021