



## RAVENOL ATF M 6-Serie



ART.-NR. 1212105

1 L	1212105-001
4 L	1212105-004
10 L	1212105-010
20 L	1212105-020
20 L	1212105-B20
60 L	1212105-060
60 L	1212105-D60
208 L	1212105-208
208 L	1212105-D28
1000 L	1212105-700

**FABRICATION SYNTHETIC**  
**APPROVALS MB-APPROVAL 236.10 (A 001 989 21 03)**  
**RECOMMENDATIONS CHRYSLER 52107891AA**

### ATF Professional Line

**RAVENOL ATF M-6 Serie** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF M-6 Serie** is one of the ATF (Automatic Transmission Fluid) for all 5-motion automatic transmission of Mercedes Benz with controlled torque converter lockup clutch AG 722.6 and AG 722.7.

**RAVENOL ATF M 6-Serie** guarantees a maximum wear protection in every operating state.

## Application Notes

**RAVENOL ATF M-6 Serie** was developed for use automatic transmission, especially for 5-gear transmission with with controlled torque converter lockup clutch AG 722.6 and AG 722.7 from Mercedes Benz.

## Characteristics

**RAVENOL ATF M 6-Serie** offers:

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very low pour point
- a very good oxidation stability
- protection against wear, corrosion and foam formation
- good balanced coefficient of friction
- a neutral behaviour against sealing materials
- a neutral behaviour because of inhibition against non-ferrous metals



RAVENOL special transmission

fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

- 

**Please note:** RAVENOL

special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.

- 

Misapplication of RAVENOL

special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.

- 

Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	847,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-51	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019