



## RAVENOL Fork Oil Very Heavy 20W



**VISCOSITY** 20W

**FABRICATION** MINERAL

**RECOMMENDATIONS** YAMAHA | KAWASAKI | HONDA | APRILIA | BMW | SUZUKI | DUCATI | TRIUMPH | MOTO-GUZZI

**RAVENOL Fork Oil Very Heavy 20W** is a fork oil on mineral oil base which was developed for all forks of off-road motorbikes and motor cross bikes.

**ART.-NR. 1182106**

1 L | 1182106-001  
4 L | 1182106-004  
20 L | 1182106-020  
20 L | 1182106-B20  
1000 L | 1182106-700

**RAVENOL Fork Oil Very Heavy 20W** is especially characterised by a high and stable viscosity index as well as a solid corrosion protection. Efficient additives offer even under extreme loads an excellent corrosion protection. The behaviour against sealing materials is neutral.

## Application Notes

**RAVENOL Fork Oil Very Heavy 20W** was developed for the use in all chassis components of two-wheeler vehicles and offers good power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the mineral fork oils are miscible among each other.

## Characteristics

**RAVENOL Fork Oil Very Heavy 20W** offers:

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	869	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm <sup>2</sup> /s	10,9	DIN 51562



Property	Unit	Data	Audit
Viscosity at 40°C	mm <sup>2</sup> /s	68,0	DIN 51562
Viscosity index VI		151	DIN ISO 2909
Pourpoint	°C	-35	DIN ISO 3016
Flash point (COC)	°C	230	DIN ISO 2592
TBN	mg KOH/g	0,4	ASTM D2896
Sulphated ash	%wt.	ca. 0,06	-

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 08. August 2019