

MOL Netsol AF 2

antifoam additive



MOL Netsol AF 2 is an antifoam agent containing no silicone oil. It is desirable to pre-dilute the product in the emulsion to be treated prior to the application. Recommended concentration for application: 0.01-0.1 % (V/V). To be shaken prior to use!

Application



Post treatment of water-miscible metalworking fluids

Features and benefits

Ready solvency

Easy handling

High efficiency

Low application treat rate

Properties

Properties	Typical values
Appearance	white, turbid
Density at 15°C [g/cm ³]	1,008

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. To preserve the original quality keep the suggested storage temperature. During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

In the concentration specified for use and in case of keeping the health safety rules, the emulsions are not harmful to human health and do not cause skin affection.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 12 months

Recommended storage temperature: +5°C - +40°C

Ordering information

Custom Tariff Number 34039900

SAP code and packaging:

13008190 MOL Netsol AF 2 X1L

1 l plastic bottle (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.