



Mobilube™ S 80W-90

Mobil Commercial Vehicle Lube , Russia

Multi-Purpose Drivetrain Lubricant

Product Description

Mobilube™ S 80W-90 is an extra high performance drivetrain lubricant engineered to provide excellent lubrication for state-of-the-art, heavy duty manual transmission components used in on-highway commercial vehicles and cars. Potential benefits include excellent shifting performance, good low temperature fluidity, and high temperature viscosity retention. Mobilube S 80W-90 provides API GL-4/5 level performance.

Features and Benefits

Today's technology has vastly improved the performance capabilities of on-highway vehicles in terms of load, speed, and control through inno-drivetrain designs. These designs have increased the requirements of components and lubricants to deliver a higher level of performance. For heavy-duty applications, friction control, wear reduction, thermal stability, shear stability, rust and corrosion inhibition, and seal protection are features that must be optimally balanced to contribute to long gear and synchroniser life, smooth shift control, fuel economy, and high load capability over a wide range of applications. Mobilube S 80W-90 delivers outstanding performance in current as well as older units. The key benefits include:

Features	Advantages and Potential Benefits
Outstanding load carrying, anti-wear, and extreme pressure performance	Helps to promote long transmission life.
Excellent prevention of deposits and lacquer formation	Helps to promote long seal life, extended drain, and service intervals
Excellent protection from corrosion of copper and its alloys	Helps to promote long life of synchronisers and smoother shifting performance
Effective thermal and oxidation resistance at high operating temperatures	Helps to promote reduced wear and long component life
Excellent shear stability	Maintains effective viscosity and film strength during severe operation
Good low-temperature fluidity	Easier, smoother shifting and quicker starts

Applications

Recommended by ExxonMobil for use in:

- Cars, on highway light and heavy duty trucks, busses, and vans
- Heavy duty automotive type drivetrains where API GL-4/GL-5 level performance is required

Specifications and Approvals

Mobilube S 80W-90 meets or exceeds the requirements of the following industry specifications:	
API GL-5 / MT-1	X
Scania STO 1:0	X
ISUZU Axle Oil	X
SUZU Large Manual Transmission Oil	X
BOSCH TE-ML 08	X

According to ExxonMobil, Mobilube S 80W-90 is of the following quality level:	
ZF-TE-ML 07A/08	X

Mobilube S 80W-90 has the following builder approvals:	
MAN 341 Typ Z2	X
MAN 342 Typ M2	X
ZF-TE-ML 02B/05A/12L/12M/16B/17H/19B/21A	X
MB-Approval 235.0	X
MACK GO-J	X

Mobilube S 80W-90 is recommended by ExxonMobil for use in applications requiring:	
API GL-4	X
Meritor O-76-D	X
MAN 341 Typ E2	X

Military:	
MIL-PRF 2105E quality level, but not approved	

Typical Properties

Mobilube S 80W-90	
SAE Grade	80W-90
Viscosity, ASTM D 445	
cSt @ 40°C	144
cSt @ 100°C	15.0
Viscosity Index, ASTM D 2270	105
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	210
Density @ 15°C kg/l, ASTM D 4052	0.90

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

Mobil Oil Lubricants LLC : 123242, Moscow, Novinsky boulevard, 31, Russia

+ 7 (095) 232 22 23

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.ru/ru-ru/contact->

[us-technical](#)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved