





## **RAVENOL Professional Radiator Stop Leak**



ART.-NR. 1390301

300 ml | 1390301-300

**RECOMMENDATIONS** NEUTRAL GEGEN GUMMI, KUNSTSTOFFE, LEICHT- UND BUNTMETALLE | VOLL VERTRÄGLICH MIT FROSTSCHUTZMITTELN UND KÜHLFLÜSSIGKEITEN

Sealant for the cooling system.

**RAVENOL Professional Radiator Stop Leak** is a dispersion for protecting the cooling system and the combustion chamber against leaks and increasing operational safety.

**RAVENOL Professional Radiator Stop Leak** permanently seals hairline cracks and leaks.

**RAVENOL Professional Radiator Stop Leak** prevents seals from sweating and the loss of coolant.

**RAVENOL Professional Radiator Stop Leak** is suitable for closed cooling systems.

## **Application Notes**

**RAVENOL Professional Radiator Stop Leak** is added to the radiator. If there are filters in the cooling system, a radiator jointing material may not be used.

Area of application:

- Severe sweating of cylinder head gaskets
- Leaky hose connections
- Hairline cracks in the radiator, cylinder head or engine block

<u>Application:</u> **RAVENOL Professional Radiator Stop Leak** suffices for 10 I of coolant. Open the heating valve completely. The engine should be at operating temperature.

Shake the can and fill the content into the cooling system with the engine running. Add coolant.

After filling, allow the engine to continue to run for at least 10 min. or take a test drive. Check the system's coolant level, absence of air and leak tightness.

For lorry radiators mix ratio max. 1:100.

RAVENOL Professional Radiator Stop Leak is also suitable for closed cooling systems.







## **Characteristics**

RAVENOL Professional Radiator Stop Leak provides:

- Protection against sweating cylinder head gaskets
- Sealing of hairline cracks and leaks in the cooling system

Property	Unit	Data	Audit
Density at 20°C	kg/m³	1020	EN ISO 12185
Colour		grünblau	visual
Smell		citrus	-
pH-Value		9,5	DIN 19268

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020