

MOL Farm Protect 15W-40

multigrade diesel motor oil



MOL Farm Protect 15W-40 is an engine oil consisting of mineral oils produced using modern oil refining processes and containing a high performance balanced additive system that improves the flow characteristics.

Application



High performance engines of tractors and self-propelled agricultural machines

Irrigation equipment, units

Hydraulic systems where application of engine oil is specified by the manufacturer

Features and benefits

Excellent wear protection

Improves engine reliability and provides protection to critical engine parts

Exceptional thermal and oxidation stability

Resists the ageing process and deposit formation, even at high operating temperatures, giving long oil lifetimes and reduced maintenance costs

Excellent shear stability

Maintains its favourable properties for a long period even under heavy loads and shear stresses

High-level reserve of alkalinity

Persistent acid neutralization, giving a long oil drain interval

Excellent soot handling

Protection against soot deposits and bore polishing

Specifications and approvals

Viscosity grade: SAE 15W-40
ACEA E7-12
API CI-4/SL
MAN M 3275-1
Volvo VDS-3
Tatra TDS 30/12
Renault RLD-2
MTU Type 2
Caterpillar ECF-2
MACK EO-M Plus
Deutz DQC III-10
KAMAZ

MOL Farm Protect 15W-40

multigrade diesel motor oil



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,885
Kinematic viscosity at 40°C [mm ² /s]	113,5
Kinematic viscosity at 100 °C [mm ² /s]	14,7
Viscosity index	134
Pour point [°C]	-30
Flash point (Cleveland) [°C]	225
Base number (BN) [mg KOH/g]	10,9

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13007247	MOL Farm Protect 15W-40 10LA	10 l plastic can
13007068	MOL Farm Protect 15W-40 50KG	60 l steel drum
13007079	MOL Farm Protect 15W-40 180KG	216.5 l steel drum

Order booking:

Please contact your local distributor or sales partner for ordering details.