

MOL Forest 150

chain-saw lubricating oil



MOL Forest 150 is a high quality chain lubricating oil, containing additives that prevent scuffing and improve adhesion, inhibit oxidation and corrosion, developed for state-of-art chain saws.

Application



Hand chainsaws used for logging

Features and benefits

Excellent wear protection

Wear of chain elements, teeth and the guide bar are reduced
Long chain lifetime

Excellent adhesion, strong tackiness

Enables economical use

Excellent cold flow properties

Suitable for logging throughout the year

Specifications and approvals

Viscosity grade: ISO VG 150

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,891
Kinematic viscosity at 40°C [mm ² /s]	151
Kinematic viscosity at 100 °C [mm ² /s]	14,8
Viscosity index	97
Pour point [°C]	-18
Flash point (Cleveland) [°C]	245

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

MOL Forest 150

chain-saw lubricating oil



Ordering information

Custom Tariff Number 27101999

SAP code and packaging:

13009151 MOL Forest 150 180KG

216.5 l steel drum (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.