



RAVENOL ATF SP-IV RR



ART.-NR. 1211138

1 L | 1211138-001
4 L | 1211138-004
20 L | 1211138-020
20 L | 1211138-B20
60 L | 1211138-060
60 L | 1211138-D60
1000 L | 1211138-700

FABRICATION SYNTHETIC

RECOMMENDATIONS HYUNDAI 00232-19052 | HYUNDAI 04500-00117 | HYUNDAI EQUUS | HYUNDAI GENESIS | HYUNDAI GENESIS COUPE | KIA MOHAVE | KIA QUORIS

RAVENOL ATF SP-IV RR is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition with excellent thermal and oxidation stability and adhesion factor performance which ensure a perfect function of the automatic transmission.

RAVENOL ATF SP-IV RR demonstrates excellent flow properties at low temperatures.

RAVENOL ATF SP-IV RR is a new generation ATF (Automatic-Transmission-Fluid) for 8-speed automatic transmissions of Hyundai and KIA. Guarantees maximum wear protection in every operating Status.

Application Notes

RAVENOL ATF SP-IV RR was specially developed for 8-speed automatic transmissions of Hyundai and KIA. Please follow manufacturer's recommendations.

Characteristics

RAVENOL ATF SP-IV RR offers:

- Very good lubricant properties, even in low winter temperatures
- High, stable viscosity index
- High thermal and oxidative stability
- Excellent protection against wear, corrosion and frothing
- Excellent friction coefficient consistency
- Excellent cooling properties

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to



malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	835,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-51	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 22. August 2019