# **MOL Turbo S 20W-20**

## monograde diesel motor oil



MOL Turbo S 20W-20 is a product produced from mineral oil using additives that ensure a state-of-art performance level, including components for modifying the flow characteristics.

#### **Application**







Gear drives, torque converters and hydraulic systems

#### **Features and benefits**

Good detergent-dispersant properties

Prevents formation of lacquer and sludge type deposits

Excellent shear stability

Preserves viscosity properties during the entire oil change period

#### **Specifications and approvals**

Viscosity grade: SAE 20W-20 ACEA E2-96 Issue 5 API CF-4/SJ MAN 270 Volvo VDS

#### **Properties**

Properties	Typical values
Density at 15°C [g/cm3]	0,886
Kinematic viscosity at 40°C [mm2/s]	62,3
Kinematic viscosity at 100 °C [mm2/s]	8,6
Viscosity index	103
Pour point [°C]	-30
Flash point (Cleveland) [°C]	225
Base number (BN) [mg KOH/g]	7,3

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages. In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

1 / 2 Page.

Version: 003.002.002

# **MOL Turbo S 20W-20**

## monograde diesel motor oil



## **Ordering information**

Custom Tariff Number 27101981

SAP code and packaging:

13009264 MOL Turbo S 20W-20 180KG 13009263 MOL Turbo S 20W-20 216.5 I steel drum (for order only) Road tank car (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.

2 / 2 Page.

Version: 003.002.002