

MOL ATF

automatic transmission fluid



MOL ATF is an automatic transmission fluid produced from mineral base oils made using unique oil refining processes, and containing additives that comply with stringent quality requirements.

Application



Automatic transmissions of passenger cars and light commercial vehicles

Hydraulic servo equipment

Fork-lift trucks, cranes

Marine gears

Features and benefits

Optimal friction characteristics

Precise and noiseless switching between gears
Convenient and economical operation

Good thermal and oxidation stability

Reliable operation, so reduced operational costs

Good wear protection

Contributes to increasing equipment lifetime

Excellent shear stability

Sustains lubricity during long oil drain intervals

Specifications and approvals

MAN 339 Typ L2
MAN 339 Typ V1
MAN 339 Typ Z1
ZF TE-ML 04D[ZF001251]
ZF TE-ML 14A[ZF001251]
ZF TE-ML 17C[ZF001251]
Voith H55.6335
GM Dexron-IID
GM Type A Suffix A
Ford Mercon
ZF TE-ML 02F
ZF TE-ML 03D
ZF TE-ML 05L
ZF TE-ML 09
ZF TE-ML 11A
Allison C-4

MOL ATF

automatic transmission fluid



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,863
Kinematic viscosity at 40°C [mm ² /s]	37,7
Kinematic viscosity at 100 °C [mm ² /s]	7,6
Viscosity index	175
Pourpoint [°C]	-42
Flash point (Cleveland) [°C]	210

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101987

SAP code and packaging:

13006041	MOL ATF X1L	1 l plastic bottle
13010073	MOL ATF 10LA	10 l plastic can (for order only)
13009339	MOL ATF 47KG	60 l steel drum
13009355	MOL ATF 170KG	216.5 l steel drum
13009022	MOL ATF	Road tank car (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.