

MOL Hykomol Syntrans V 75W-90

synthetic automotive gear oil



MOL Hykomol Syntrans V 75W-90 is a multigrade gear oil produced from a high performance synthetic base oil, using a modern complex additive system that ensures extended oil change intervals and reliable operation.

Application



Manual gearboxes in modern passenger cars, SUVs and light commercial vehicles

Features and benefits

| | |
|---------------------------------|---|
| Outstanding oxidation stability | Enables long drain interval application |
| Low coefficient of friction | Good efficiency and low fuel consumption |
| Excellent thermal stability | Prevents formation of sludge and deposits, so servicing needs are reduced |
| Excellent cold flow properties | Fuel-saving operation at low temperature |
| Low foaming tendency | Continuous, stable lubricating film, even at high speeds |
| Excellent wear protection | Long gear lifetime, giving reliable operation |

Specifications and approvals

Viscosity grade: SAE 75W-90
API GL-4
VW 501 50

Properties

| Properties | Typical values |
|--|----------------|
| Density at 15°C [g/cm ³] | 0,858 |
| Kinematic viscosity at 40°C [mm ² /s] | 102 |
| Kinematic viscosity at 100 °C [mm ² /s] | 15,0 |
| Viscosity index | 176 |
| Pour point [°C] | -45 |
| Flash point (Cleveland) [°C] | 215 |

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Hykomol Syntrans V 75W-90

synthetic automotive gear oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 34031980

SAP code and packaging:

13301977 MOL Hykomol Syntrans V 75W-90 50KG

60 l steel drum (for order only)

13300572 MOL Hykomol Syntrans V 75W-90 170KG

216.5 l steel drum

Order booking:

Please contact your local distributor or sales partner for ordering details.