



RAVENOL SVP Stand. Viscos. Perform. Oil SAE 15W-40



ART.-NR. 1117100

1 L | 1117100-001
5 L | 1117100-005
20 L | 1117100-020
20 L | 1117100-B20
1000 L | 1117100-700

VISCOSITY 15W-40

SPECIFICATIONS API SJ | API CF | ACEA A3 | ACEA B4

FABRICATION MINERAL

RECOMMENDATIONS MAN 271 | ZF TE-ML 07C | VW 505 00

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is particularly recommended for vehicles with high mileage petrol and diesel engines with and without turbocharge and direct injection. The mineral motor oil **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

The extremely conditioning and cleaning agents in **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

Application Notes

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed. **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Characteristics

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 offers:

- High wear protection, important for large mileages and inadequate oil changes
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	873	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	14,4	DIN 51 562
Viscosity at 40°C	mm ² /s	107,2	DIN 51 562
Viscosity index VI		137	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flash point	°C	240	DIN ISO 2592
TBN	mg KOH/g	8,9	ASTM D2896
Sulphated ash	%wt.	1,1	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 04. May 2021