



RAVENOL ATF Fluid



ART.-NR. 1213101

1 L | 1213101-001
4 L | 1213101-004
10 L | 1213101-010
20 L | 1213101-020
20 L | 1213101-B20
1000 L | 1213101-700

FABRICATION MINERAL

RECOMMENDATIONS TYPE A SUFFIX A (TASA) | ALLISON C-4 | MAN 339
TYP A | MB 236.2 | RENK DOROMAT | CAT-TO-2

RAVENOL ATF Fluid is designed on the basis of refined base oils with a special additive and inhibition, which guarantee a perfect function.

RAVENOL ATF Fluid is a very high quality mineral gear fluid for automatic fluid couplings and torque converters as well as power steering aids.

Application Notes

RAVENOL ATF Fluid should be used according to the instructions of the unit manufacturer in: Automatic transmissions, turbo couplings, servo clutches and other hydrostatic and hydrodynamic systems.

RAVENOL ATF Fluid must not be used if ATF Type DEXRON B or DEXRON D or ATF Type M2C-33 E / F / G are expressly mentioned as filling instructions.

Characteristics

RAVENOL ATF Fluid offers:

- Exceptionally good resistance to aging
- A very good viscosity-temperature behavior
- Effective protection against wear
- Very good oxidation stability and low foaming tendency
- Enhanced protection against corrosion
- An extremely low pour point
- Compatible with all types of sealing materials
- Miscibility and compatibility with all brands of ATF's with Type A Suffix A specification



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	848,0	EN ISO 12185
Colour		rot	visual
Viscosity at 100°C	mm ² /s	7,4	DIN 51 562
Viscosity at 40°C	mm ² /s	34,6	DIN 51 562
Viscosity index VI		187	DIN ISO 2909
Pourpoint	°C	-48	DIN ISO 3016
Flash point	°C	210	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 23. August 2019