



## RAVENOL TTC Premix -40°C Protect C11



**RECOMMENDATIONS** VW TL 774-C (ENTSPRICHT G11) | MAN 324NF | AFNOR R15-601 (FRANKREICH) | BS 6580 (GB) | CUNA NC 956-16 (ITALIEN) | JIS K 2234 (JAPAN) | O NORM V 5123 (ÖSTERREICH) | UNE 25-361 (SPANIEN) | ASTM D1384 | ASTM D 2570 | ASTM D2809 | ASTM D3306 TYPE 1 | ASTM D4985 | ASTM D6210 TYP I-FF | SAE J1034 | CHRYSLER MS-7170 | FIAT 9.55523 | FIAT PARAFLU 11 | FORD WSS-M97B51-A1 | IVECO 18-1830 | SUZUKI

### ART.-NR. 1410105

1,5 L | 1410105-150  
5 L | 1410105-005  
10 L | 1410105-010  
20 L | 1410105-020  
20 L | 1410105-B20  
1000 L | 1410105-700

**RAVENOL TTC Premix -40°C Protect C11** is a ready to use, prediluted eco-friendly 1.2- Ethanediol (monoethylene glycol) based nitrite, amine and phosphate-free coolant for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. The product is formulated as a long-term coolant based on a proven inhibitor development. The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL TTC Premix -40°C Protect C11** protects the cooling system from rust, frost, and in summer, from overheating.

## Application Notes

**RAVENOL TTC Premix -40°C Protect C11** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL TTC Premix -40°C Protect C11** to radiator to fill line.

## Characteristics

**RAVENOL TTC Premix -40°C Protect C11** offers:

- Excellent for light metal engines
- Good reserve alkalinit
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	1080	EN ISO 12185
Colour		gelb-grün fluoreszent	visual



Property	Unit	Data	Audit
Flash point	°C	142	-
pH-Value		7,8	ASTM D 1287
Freezing point	°C	-40°C	ASTM D 1177

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 13. January 2020