


MOL Ultrans Synt 320 WS

synthetic industrial gear oil



MOL Ultrans Synt 320 WS is a polyalkylene glycol (PAG) based premium quality industrial gear oil having a balanced combination of additives that ensure high performance. It provides a much higher degree of protection for drive gears compared with conventional mineral based gear oils. Its application is accompanied by a potential energy saving. It is soluble in water, it is free from chlorine, lead and sulphur. Due to its high thermal stability it can be used at temperatures exceeding 200 °C. It cannot be blended with mineral oil or hydrocarbon based synthetic oils! It is compatible with the most frequently used sealing materials. In case of particularly high temperatures, it is recommended to use nitrile rubber (NBR), fluor-silicone or vinyl-methyl polysiloxane (Q) sealing materials. Polyurethane sealing materials should be avoided. The usual industrial paint coatings become soft upon contact with the product. Ideally, the internal surface of the drive gear is not painted, or is coated with resistant material, e.g. two layers of epoxy coating.

Application



Industrial gear drives operating under arduous conditions (high loads, low speeds)

Enclosed industrial gear drives working at permanently high operating temperatures

Gear drives exposed to shock loads

Bearings operating at high temperatures

Worm gears

Lubrication of reciprocating and screw compressors, chains, conveyors, kilns

Features and benefits

Excellent load-carrying properties

No lubricating film disruption even under shock loads, giving protection against seizure

Exceptional thermal and oxidation stability

Increased oil drain intervals; three times longer drain periods are achievable compared to conventional lubricants, depending on the operating conditions
Operational, maintenance and disposal costs are reduced
Increased operational safety, availability and lifetime of equipment

Low coefficient of friction

Good efficiency and low energy consumption

Excellent protection against micropitting

High load-carrying ability, giving long gear lifetimes

Excellent cold flow properties

Reliable operation even at low temperatures

Specifications and approvals

Viscosity grade: ISO VG 320
DIN 51502 PG-CLP
DIN 51517-3: CLP-PG
David Brown Type G

MOL Ultrans Synt 320 WS

synthetic industrial gear oil



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	1,062
Kinematic viscosity at 40°C [mm ² /s]	305
Kinematic viscosity at 100 °C [mm ² /s]	60,6
Viscosity index	252
Pour point [°C]	-39
Flash point (Cleveland) [°C]	282
Antiwear properties (FZG)	
- failure load stage	>12

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 34039900

SAP code and packaging:

13009331 MOL Ultrans Synt 320 WS 10LA
13006655 MOL Ultrans Synt 320 WS 205KG

10 l plastic can (for order only)
216.5 l steel drum (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.