

# MOL Farm STOU 10W-30

## universal tractor oil



MOL Farm STOU 10W-30 is a STOU type universal tractor oil produced from synthetic and highly refined mineral oil, using a complex additive system that meets the needs of tractors.

### Application



Torque converters, capable of shifting gears under load (John Deere Direct Drive, Powershift), and drive elements of agricultural and construction machines

AGCO (Fendt) Vario gearboxes

Engines of tractors and self-propelled agricultural machines, for which the OEM specification is listed in the Specifications and Approvals section

Hydrostatic drives

### Features and benefits

Excellent wear protection

Optimal friction characteristics

Excellent corrosion protection

Good thermal and oxidation stability

Improved cold flow properties

Long gear lifetime, giving reliable operation

Wet breaks and clutches operate silently and judder-free

Long-term protection against surface damage, even in the presence of moisture

No deposit or sludge formation  
Reliable operation, so reduced operational costs

Reliable operation even at low temperatures

### Specifications and approvals

Viscosity grade: SAE 10W-30

ACEA E3-96 Issue 4

API CG-4

API GL-4

Ford ESN M2C159-B/C

Caterpillar TO-2

ZF TE-ML 06B

ZF TE-ML 06C

ZF TE-ML 07B

Allison C-4

John Deere JDM J20C

John Deere JDM J27

Massey-Ferguson M1145

Massey-Ferguson M1144

White-Farm Q-1826

Eaton (Vickers) M-2950-S

Eaton (Vickers) I-280-S

# MOL Farm STOU 10W-30

## universal tractor oil



### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,880
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	68,6
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	10,8
Viscosity index	147
Pour point [°C]	-36
Flash point (Cleveland) [°C]	220

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 27101981

#### SAP code and packaging:

13011030 MOL Farm STOU 10W-30 10LA  
13010802 MOL Farm STOU 10W-30 180KG

10 l plastic can (for order only)  
216.5 l steel drum (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.