



PROSYLVA 4T SYN 10W-40



Semi synthetic lubricant, designed for 4 stroke gasoline engines used in severe applications of mechanized farming.

SPECIFICATIONS AND APPROVALS

International specifications

ACEA A3

API SL

APPLICATIONS

TOTAL PROSYLVA 4T SYN 10W-40 is particularly adapted to **4 stroke gasoline engines**, for **gardening** and **mechanized farming** working under continuous **heavy loads** and at **high temperature**.

PERFORMANCES AND CUSTOMER BENEFITS

High quality synthetic base stocks combined with high-performance additives offer **outstanding thermal stability**, ensuring efficient lubrication of hot engine parts.

Its **exceptional oil film resistance when hot** guarantees good engines operation and no performance losses.

TOTAL PROSYLVA 4T SYN 10W-40 contains **excellent viscosity stability** in service, providing **smooth cold starts**.

The **association of detergent, dispersant and anti-wear additives** keeps the engine clean and enables effective control of soot, sludge and piston deposits.

Its **anti-rust and anti-corrosion properties** protect the engine from moisture damages.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL PROSYLVA 4T SYN 10W-40

		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	873
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	96.8
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	14.8
Viscosity Index	-	ASTM D2270	160
Pour Point	°C	ASTM D97	-24
T.B.N	mgKOH/g	ASTM D2896	10.4

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS

562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL PROSYLVA 4T SYN 10W-40

Update 07/2014

www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com