

MOTO RACING 4T 10W50



MOTORCYCLE

Lubricants

Description

It is the ideal synthetic oil lubricant oil for very high performance 4-stroke engines. Its formula ensures maximum protection for all engine components, with special emphasis on the clutch and gearbox. Its efficiency is reflected in the very low friction experienced by the engine's components, whilst always maintaining maximum power. The results have been proven with race-ready and standard motorcycles at the highest levels of national and international competition whilst performing in extreme conditions. It performs equally well on the road and on the racetrack.

Properties

- Results tested on high performance 4-stroke engines in extreme conditions.
- Perfect control of the sliding of the clutch discs and protection of the gearbox in the joint lubrication systems of the engine and wet clutch.
- The base oils and additives used minimise wear and ensure a longer engine-life.
- Delivers excellent thermal stability enabling less oil deterioration and more efficient engine running.
- Ensures a minimum oil consumption thanks to the reduced volatility of the components used in its formulation.

Quality levels

- API SN
- JASO T 903:2016 MA2

Technical characteristics

	UNIT	METHOD	VALUE
SAE grade	-	-	10W50
Density at 15 °C	g/cm ³	ASTM D 4052	0,856
Viscosity at 100 °C	cSt	ASTM D 445	18.25
Viscosity at 40 °C	cSt	ASTM D 445	124
Viscosity at -25 °C	cP	ASTM D 5293	7000 max
Viscosity index	cP	ASTM D 2270	166
Flash point, open cup	°C	ASTM D 92	246
Freezing point	°C	ASTM D 97	-30 max
T.B.N.	mg KOH/g	ASTM D 2896	7.5
Sulphated ash	% in weight	ASTM D 874	1.2 max

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 6. April 2018.