



RAVENOL Performance Truck SAE 10W-40



VISCOSITY 10W-40

SPECIFICATIONS API CI-4 | API CF | ACEA E4 | ACEA E7

FABRICATION SEMI-SYNTHETIC

APPROVALS DEUTZ DQC III-10 | MACK EO-N | MAN M 3277 | MB-APPROVAL 228.5 | MTU TYP 3 | RENAULT RVI RXD/RLD-2 | SCANIA LDF-2 | TEDOM 258-4 (61-0-0258) | VOLVO VDS-3 | LICENSE: API CI-4

RECOMMENDATIONS DAF HP1/2 | SCANIA LDF-3 | MACK EO-M PLUS | VOITH RETARDER B | GLOBAL DHD-1

ART.-NR. 1122106

1 L	1122106-001
5 L	1122106-005
10 L	1122106-010
20 L	1122106-020
20 L	1122106-B20
60 L	1122106-060
60 L	1122106-D60
208 L	1122106-208
208 L	1122106-D28
1000 L	1122106-700

RAVENOL Performance Truck SAE 10W-40 is semi-synthetic multi-grade diesel engine oil for highly loaded diesel engines based on MC-systems.

RAVENOL Performance Truck SAE 10W-40 is low-friction long-life engine oil for all kind of diesel engines with and without turbocharging in trucks, buses and machinery. Suitable for the longest oil change intervals.

Application Notes

RAVENOL Performance Truck SAE 10W-40 has a higher performance than conventional high-performance engine oils. International such oils are called UHPD oils (UHPD = Ultra High Performance Diesel Oil). Regardless of the particular mileage, older diesel engines on **RAVENOL Performance Truck SAE 10W-40** should be changed without rinsing.

Characteristics

RAVENOL Performance Truck SAE 10W-40 offers:

- High wear protection even under constant load at full throttle
- Reduced fuel consumption by low-friction characteristics
- Quick oil circulation reduces cold-start and warm-up wear
- Protection against bore polishing of cylinder paths
- Reduction of exhaust particles
- Protects against corrosion, even when using diesel fuels with high sulfur content
- Safe protection against deposits and sticking, both under extreme thermal loads and short haul
- Optimum compatibility with seal materials
- Environmentally friendly due longest oil change intervals and low evaporation losses



- Guaranteed extended drain intervals for the long-haul truck or transport

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	866,0	EN ISO 12185
Colour		dunkelbraun	visual
Viscosity at 100°C	mm ² /s	14,5	DIN 51 562
Viscosity at 40°C	mm ² /s	96,2	DIN 51 562
Viscosity index VI		156	DIN ISO 2909
Pourpoint	°C	-33	DIN ISO 3016
Flash point	°C	234	DIN ISO 2592
TBN	mg KOH/g	13,2	ASTM D2896
Sulphated ash	%wt.	1,7	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 21. July 2021