

# MOL WO M 15

## medicinal and cosmetic white oil



MOL WO M 15 is a high purity, mineral-oil based product, produced by a multiple stage refining of white oil. It does not contain aromatic compounds. It complies with the most important specifications for white oil, such as the provisions about Paraffinum liquidum in the European Pharmacopoeia and the Hungarian Pharmacopoeia, and it exceeds the requirements for cleanliness by the American Food and Drug Administration (FDA) 172.878 and 178.3620(a) standards.

### Application



- Manufacturing of pharmaceutical products
- Manufacturing of vaccines
- Manufacturing of cosmetic products
- Manufacturing of foodstuffs
- Auxiliary material for the canning industry
- Equipment in possible food contact

### Features and benefits

- |                            |   |
|----------------------------|---|
| High cleanliness           | Chemically neutral, meets the most severe purity requirements<br>No health damage is caused upon direct contact with living organisms, when instructions are followed |
| Colourless and odourless   | The colour and odour of product is not changed  |
| Free of aromatic compounds | Safe use  |

### Specifications and approvals

- Viscosity grade: ISO VG 15
- KOSHER*
- HALAL*
- OÉTI: 2839-2/1996*
- European Pharmacopoeia (Ph.Eur. Curr.revision)
- Ph. Hg. VIII (Pharmacopoeia Hungarica)
- FDA 172.878
- FDA 178.3620(a)

# MOL WO M 15

## medicinal and cosmetic white oil



### Properties

Properties	Typical values
Appearance	colourless, bright, clear
Colour (Saybolt)	+30
Density at 15°C [g/cm <sup>3</sup> ]	0,848
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	16,2
Dynamic viscosity at 20 °C [mPa.s]	32
Pour point [°C]	-12
Flash point (Cleveland) [°C]	190

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 36 months

Recommended storage temperature: max. 35°C

### Ordering information

Custom Tariff Number 27101985

#### SAP code and packaging:

13007019	MOL WO M 15 X10L	10 l plastic can
13006667	MOL WO M 15 170KG	216.5 l steel drum
13006668	MOL WO M 15 860KG	IBC (for order only)
13006666	MOL WO M 15	Road tank car (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.