

Fully Synthetic

Kixx D1 A3/B4

High grade diesel engine oil, the perfect fit for ACEA A3/B4 specification

ACEA A3/B4-07, E7-08



DESCRIPTION

Kixx D1 A3/B4 is engineered for hard-working gasoline and diesel engines. It is a high performance, HVI engine oil that provides unsurpassed lubrication with a wide range of temperature for today's gasoline and diesel RV engines operating under severe conditions.

APPLICATIONS

- Gasoline, diesel powered RV and SUV built by Mercedes Benz, Ford, GM etc
- Diesel engine of Cummins, Duramax and Navistar – for bigger, heavier duty truck application, such as delivery vans and utility fleets
- Mixed fleets of European, North American diesel engines (High speed, four-stroke, turbocharged and EGR)
- Commercial road transport, including the latest electronic controlled engines
- Stop-and-go vehicles in high soot loading service such as buses and waste collection trucks

PERFORMANCE STANDARDS

- ACEA A3/B4-07, E7-08
- API CI-4/SL

CUSTOMER BENEFITS

- Maximize engine life based on outstanding wear protection
- Exceptional high temperature protection for hot running engines under heavy load
- Excellent low temperature fluidity for quick and easy start-ups in cold weather
- Keeps engine clean through outstanding resistance to high temperature varnish and low temperature sludge deposit formation

KEY PROPERTIES

SAE Grade	10W-40
Density, kg/L @15°C	0.861
Kinematic Viscosity, mm ² /s @ 40°C	103.9
Kinematic Viscosity, mm ² /s @ 100°C	15.2
Viscosity Index	155
Pour Point °C	-42
Flash Point °C	228
Package (Liters)	200