

# MOL EcoClean-S

## engine degreaser



MOL EcoClean-S is a solvent based degreasing liquid containing a high quantity of active ingredients.

### Application:

- Apply the product on the surface to be treated by means of brushing, spraying or immersing.
- It will loosen or dissolve the contamination of the surface during 15-20 minutes of soaking.
- Then wash the surface with abundant water to remove it, together with the contamination.
- Dry the surface as necessary after washing, or wipe the surface with a soft cloth. If the surface is heavily contaminated, it is recommended to use repeated soaking and washing.

## Application



Cleaning of vehicle surfaces contaminated with oil, grease or bitumen

Cleaning of railway tank wagons and underground tanks

Removal of chip residues from surfaces following metalworking processes

## Features and benefits

High active ingredient content

Efficiently removes even the most tenacious deposits

Ready miscibility with water

Easy to rinse off

## Properties

Properties	Typical values
Appearance	light green clear liquid
Density at 15°C [g/cm <sup>3</sup> ]	0,783
Fire point (Cleveland) [°C]	250
Flash point (Pensky-Martens) [°C]	61
Appearance of emulsion (10%V/V) / 20 nK° water	milky white colored

The characteristics in table are typical values of the product and do not constitute a specification.

## Storage and handling instructions

Should be stored in its original packaging with airtight sealing, separately from foods, in a place protected against water and sunshine, locked away from children.

In the original container under the recommended storage conditions: 24 months

Recommended storage temperature: max. 30°C

## Ordering information

Custom Tariff Number 34022090

### SAP code and packaging:

19004233 MOL EcoClean-S 10L

10 l plastic can (for order only)

19002303 MOL EcoClean-S 160KG

216.5 l steel drum (for order only)

### Order booking:

Please contact your local distributor or sales partner for ordering details.