



## RAVENOL Marinefett



ART.-NR. 1340128

100 g | 1340128-100

15er 1340128-080

80g |

400 g | 1340128-400

[Transla [Translate to  
te to EnEnglish:]

glisch:] |

[Transla [Translate to  
te to EnEnglish:]

glisch:] |

**SPECIFICATIONS** DIN 51 502: KP2K-30 |ISO 6743 PART 9: ISO-L-XCCFB2

**RAVENOL Marinefett** is a yellow-green, fluorescent, sea-water resistant lubrication grease with long-term adhesion properties. It is based on a special, calcium soap and a high-viscous synthetic base oil, as well as specifically selected active ingredients to protect against oxidation, rust and corrosion.

**RAVENOL Marinefett** is a high-pressure grease with exceptionally good adhesion and threading properties. Bearing wear is effectively reduced even under extreme loads.

**RAVENOL Marinefett** is extremely water-resistant and particularly resistant against washing out from bearings, sliding points and metal surfaces.

**RAVENOL Marinefett** provides protections against corrosion for ship parts that are exposed to seawater.

**RAVENOL Marinefett** is preferred in the marine sector.

However, it can also be used wherever a calcium-soaped grease is required - in industry, for motor vehicles, by do-it-yourselfers and in the home.

## Application Notes

**RAVENOL Marinefett** is used as boat grease for external parts of ships that are exposed to saline air humidity and direct contact with seawater and require a high degree of rust and corrosion protection. (e.g. periscopes and turret hatch closures of submarines).

**RAVENOL Marinefett** can be used for external lubrication in industry and farming, e.g. machines, metal parts, joints, wire ropes that are exposed to damp air, wet mine conditions or usual environmental influences.

**RAVENOL Marinefett** can be used to lubricate sliding and rolling bearings, guides, control levers and water pumps that are exposed to thermal and mechanical normal loaded. Also for greasing and protecting vehicle parts at risk of rusting (engine compartment, doors, car boot, welding seams, cavities).

Any rust should be removed before applying the grease a.

**RAVENOL Marinefett** can be used over a broad temperature range and provides extremely good protection against corrosion due to its good adhesion properties.



## Characteristics

RAVENOL Marinefett offers:

- Seawater resistant
- Excellent adhesion properties
- Universal use
- Extremely shear stable
- Exceedingly excellent wear protection
- Very good mechanical and chemical stability
- Very good corrosion protection
- Very good resistance to ageing
- Good pumpability, also at low temperature

Property	Unit	Data	Audit
Colour		gelblich-grün	visual
Thickener		Calcium-Komplexseifen	-
NLGI-Class		2	DIN 51 818
DIN-Product-Classification		KP2K-30	DIN 51 502
ISO-Product-Classification		ISO-L-XCCFB2	ISO 6743 P.9
Working Temperature	°C	-30/ +120	-
Short Term up to	°C	130	-
Worked Penetration 60 strokes	mm/10 bei 25°C	265-295	ISO 21370
Corrosion (SKF Emscor dist. Water)	Corr. Degree	0	DIN 51 802
Dropping Point	°C	150	DIN ISO 2176
Copper Corrosion (24h/120°C)		1	DIN 51 811
Water Resistance (3h/90°C)	°C	0-90	DIN 51 807 T1
VKA Pressure Carrying Capacity	N	2600-2800	DIN 51 350 T.4
Kinematic Viscosity (Base Oil)	mm <sup>2</sup> /s bei 40°C	900	DIN 51562-1



All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 10. May 2021