

# MOL Super Diesel 10W-30

## multigrade diesel motor oil



MOL Super Diesel 10W-30 is state-of-art product produced from mineral base oil having excellent properties using a complex additives system that ensures high performance levels required by European and US standards.

### Application



Short and long haul bus and commercial vehicle engines  
Commercial vehicle engines operating at low and high speeds  
Engines in mining, construction and agricultural machines  
Railway and ship diesel engines operating at low speed and high load

### Features and benefits

Excellent cold flow properties	Reliable start-up, even in extreme cold conditions
Excellent shear stability	Preserves its rheological properties even under severe operating conditions and high temperatures
Outstanding detergent-dispersant properties	Preserves engine cleanliness for a long period and prevents deposition of solid contaminants
Excellent soot handling	Protection against soot deposits and bore polishing
High-level reserve of alkalinity	Persistent acid neutralization, giving improved corrosion protection

### Specifications and approvals

Viscosity grade: SAE 10W-30  
API CG-4/SJ  
API CF  
Volvo VDS

### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,871
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	74,6
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	11,3
Viscosity index	143
Pour point [°C]	-39
Flash point (Cleveland) [°C]	230
Base number (BN) [mg KOH/g]	8,6

The characteristics in table are typical values of the product and do not constitute a specification.

# MOL Super Diesel 10W-30

## multigrade diesel motor oil



### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 27101981

#### SAP code and packaging:

13009272 MOL Super Diesel 10W-30 170KG

216.5 l steel drum (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.