



RAVENOL Getriebeöl CLP 100



ART.-NR. 1332107

20L | 1332107-020

SPECIFICATIONS DIN 51 517 PART 3

RECOMMENDATIONS FZG 12 | AGMA 9005-D94 | CLEAN PANEL COKER | CINCINNATI MILACRON | S-200 OXIDATION TUBES | US STEEL 224

RAVENOL Getriebeöl CLP 100 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeöl CLP 100 has a low pour point and therefore a very good cold behaviour.

RAVENOL Getriebeöl CLP 100 is free of zinc and ash due to its formulation.

Application Notes

RAVENOL Getriebeöl CLP 100 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Characteristics

RAVENOL Getriebeöl CLP 100 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	875,0	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	11,4	DIN 51 562
Viscosity at 40°C	mm ² /s	106,3	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI		106	DIN ISO 2909
Pourpoint	°C	-21	DIN ISO 3016
Flash point	°C	242	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020