



Castrol TranSynd RD

Automatic Transmission Fluid for Heavy Duty Applications

Description

TranSynd™ RD is a premium, synthetic, universal powershift and automatic transmission fluid engineered to remain stable under the most severe conditions.

TranSynd™ RD was introduced by Allison Transmission for “Rigorous Duty” applications where extended drain intervals and reduced life cycle costs are desired in Allison 5000, 6000, 8000 and 9,000 Off-Highway Series transmissions

Advantages

- Excellent thermal and oxidation stability resists deposit formation
- High viscosity index synthetic base fluids provide superior high/low temperature performance
- Excellent shear stability, excellent corrosion and anti-foaming characteristics
- Excellent wear protection
- Allows extended drain intervals and extended filter change intervals
- One fluid for year-round use in all geographic locations, reduced used oil disposal costs

Typical Characteristics

Name	Method	Units	TranSynd™ RD
Density @ 15°C, Relative	ASTM D4052	g/ml	0.847
Appearance	Visual	-	Red
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	10.0
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	56.0
Pour Point	ASTM D97	°C	-57
Viscosity, CCS -30°C	ASTM D5293	mPa.s (cP)	4800
Flash Point, COC	ASTM D92	°C	210

Product Performance Claims

Allison TES-353
Allison C4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol TranSynd RD
03 Nov 2015
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk