

# MOL Formoil FL 28

## mould release oil



MOL Formoil FL 28 is a formwork separating auxiliary material containing highly refined mineral oil and special additives that efficiently facilitate separation. It prevents sticking of a template to the product, and guarantees easy separation. It provides temporary corrosion protection to steel templates between later applications. Application on the formwork can be done most economically by spraying, but can also be applied with rollers or brushes.

### Application



- Manufacturing of concrete tiles
- Manufacturing of concrete products
- Rod-like, sheet-like, angular, shaped articles

### Features and benefits

Application specific composition	Prevents moulded material from getting stuck to the mould Quick and easy stripping without damaging edges and vertices Formed material is free from surface defects, unevenness and oil stains
Easy to lay on surfaces	Application to the mould surface is possible by spraying, rolling or brushing
Good flow properties	Applicable both outdoors and indoors
Good corrosion protection	Prevents rusting of mould elements and increases their lifetime
Economical use	Specific lubricant demand: 50-80 m <sup>2</sup> /kg, depending on the lubrication technology and the mould material

### Specifications and approvals

ISO-L-B

### Properties

Properties	Typical values
Appearance	yellow-brown, clear
Density at 15°C [g/cm <sup>3</sup> ]	0,867
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	7,4
Pour point [°C]	- 48
Flash point (Cleveland) [°C]	120

The characteristics in table are typical values of the product and do not constitute a specification.

# MOL Formoil FL 28

## mould release oil



### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 36 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 27101999

#### SAP code and packaging:

13006234 MOL Formoil FL 28 170KG

216.5 l steel drum (for order only)

13006698 MOL Formoil FL 28 860KG

IBC (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.