

MOL Acticut ME 37

environmentally compatible cutting oil



MOL Acticut ME 37 is a special chlorine free, high performance cutting oil, developed for high productivity machining of carbon steels and heavily alloyed steels. It is a highly refined mineral oil containing additives that improve lubrication, prevent wear, provide pressure resistance, inhibit corrosion and reduce formation of oil mists. It does not contain PCB, PCT, heavy metal or barium compounds.

Application



Cutting technologies of various type and duty (turning, milling, drilling, thread machining, toothing processes etc.)

All high productivity chip forming machining operations where the large cross-section of the removed chip (cutting depth and infeed) results in high cutting forces

Alloy steels which are difficult to cut

Acid resistant and stainless steels

Bearing steel materials

Automatic and easy-to-machine steel materials

Limited applicability for machining of yellow metals due to active sulfur content

Features and benefits

Excellent lubricity in a wide range of temperatures and loads

Excellent temporary corrosion protection

Low foaming tendency

Low mist formation tendency

Widely applicable for heavy-duty machining, allowing a reduced number of cutting oils

Longer service life of tool edges, giving reduced specific tool costs
Increased chip removal, giving improved productivity and reduced manufacturing costs

Effective temporary corrosion protection of workpieces, giving reduced surface treatment costs

Forms a continuous lubricating film, giving a balanced cooling effect and lubricity
Excellent surface quality and high manufacturing precision

Safer and more comfortable working environments

Specifications and approvals

EMAG
ISO 6743-7: L-MHF

MOL Acticut ME 37

environmentally compatible cutting oil



Properties

Properties	Typical values
Appearance	sötét, vöröses, tiszta
Density at 15°C [g/cm ³]	0,879
Kinematic viscosity at 40°C [mm ² /s]	35,5
Pour point [°C]	-12
Flash point (Cleveland) [°C]	235

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 36 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101991

SAP code and packaging:

13006008 MOL Acticut ME 37 180KG

216.5 l steel drum (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.