# **MOL MSE 15W-40**

### multigrade motor oil



MOL MSE 15W-40 is engine oil produced from highly refined base oils and a balanced additive system, for use in four-stroke petrol engines of earlier design.

### **Application**





Gasoline and naturally aspirated diesel engines in passenger cars and light commercial vehicles of older construction

#### **Features and benefits**

Multigrade engine oil

Suitable for use in the summer and winter, throughout the year

Good oxidation stability

Deposit formation at high temperatures is decreased Cleaner engine

#### Specifications and approvals

Viscosity grade: SAE 15W-40

API SF/CC MIL-L-46152B

#### **Properties**

Properties	Typical values
Density at 15°C [g/cm3]	0,879
Kinematic viscosity at 40°C [mm2/s]	107
Kinematic viscosity at 100 °C [mm2/s]	14,2
Viscosity index	135
Pourpoint [°C]	-27
Flash point (Cleveland) [°C]	225
Base number (BN) [mg KOH/g]	5,1

The characteristics in table are typical values of the product and do not constitute a specification.

#### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages. In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

1 / 2 Page.

Version: 009.013.000

# **MOL MSE 15W-40**

# multigrade motor oil



## **Ordering information**

Custom Tariff Number 27101981

#### SAP code and packaging:

 13006450
 MOL MSE 15W-40 X1L
 1 I plastic bottle

 13006451
 MOL MSE 15W-40 X4L
 4 I plastic can

 13006449
 MOL MSE 15W-40 180KG
 216.5 I steel drum

 13008030
 MOL MSE 15W-40
 Road tank car (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.

2 / 2 Page.

Version: 009.013.000