



RAVENOL HJC Premix -40°C Protect FL22



RECOMMENDATIONS NISSAN ANTI-FREEZE COOLANT (L250) | MAZDA FL22 COOLANT | MAZDA 000077508E20 | MAZDA C122CL005A4X | MAZDA C100CL005A4X | FORD WSS-M97B55 (MOTORCRAFT SPECIALTY GREEN ENGINE COOLANT) | FORD VC-10-A2 | 08CLAG010S0 HONDA E COOLANT | HYUNDAI LONG LIFE COOLANT | HYUNDAI 07100-00200 | HYUNDAI 07100-00400 | HYUNDAI 00232-19010 | NISSAN KE90299934 | NISSAN KE90299944 | SUBARU COOLANT 16218 | SUZUKI LONGLIFE COOLANT

ART.-NR. 1410123

1,5 L | 1410123-150
5 L | 1410123-005
10 L | 1410123-010
20 L | 1410123-020
20 L | 1410123-B20
1000 L | 1410123-700

RAVENOL HJC Premix -40°C Protect FL22 is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without phosphates, nitrites, amines and silicate. This product is formulated based on a proven inhibitor development as an extended life radiator antifreeze.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL HJC Premix -40°C Protect FL22 protects the cooling system from rust, frost, and in summer, from overheating.

Application Notes

RAVENOL HJC Premix -40°C Protect FL22 is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL HJC Premix -40°C Protect FL22** to radiator to fill line.

Characteristics

RAVENOL HJC Premix -40°C Protect FL22 offers:

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	1082	EN ISO 12185
Colour		grün	visual
pH-Value		7,8	ASTM D 1287
Freezing point	°C	-40°C	ASTM D 1177

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 13. January 2020