


MOL Dynamic Gas Super 15W-40

mobile gas motor oil



MOL Dynamic Gas Super 15W-40 is an engine oil produced from mineral oils that have been made using modern oil refining processes, and using a multi-purpose balanced additive system, including components that modify the flow characteristics, ensuring high performance properties, for modern commercial vehicle operated with gas.

Application



Vehicles and stationary engines operating on LPG or CNG gas

Conventional gasoline or diesel, naturally aspirated or turbocharged commercial vehicles and passenger cars

Features and benefits

High-level reserve of alkalinity

Persistent acid neutralization, giving improved corrosion protection

Outstanding wear protection

Forms a tenacious lubricating film even under exposure to heavy stress

Exceptional thermal and oxidation stability

Reduces the formation of sludge at low temperatures and of deposits at high temperatures

Excellent shear stability

Preserves its rheological properties even under severe operating conditions and high temperatures

Specifications and approvals

Viscosity grade: SAE 15W-40
MAN M 3271-1
API CF-4
MB 226.9

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,880
Kinematic viscosity at 40°C [mm ² /s]	114,4
Kinematic viscosity at 100 °C [mm ² /s]	15,3
Viscosity index	140
Pour point [°C]	-27
Flash point (Cleveland) [°C]	220
Base number (BN) [mg KOH/g]	7,3

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Dynamic Gas Super 15W-40

mobile gas motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13006100 MOL Dynamic Gas Super 15W-40 180KG

216.5 l steel drum (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.