



## Mobil 1 FS 5W-30

Mobil Passenger Vehicle Lube , Russia

Advanced Full Synthetic Motor Oil

### Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection. The Mobil 1 technology keeps your engine running like new. Mobil 1™ FS 5W-30 is an advanced performance synthetic engine oil designed to help provide exceptional cleaning power and provides improved protection against variable fuel quality (1).

(1)Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

### Features and Benefits

Mobil 1™ FS 5W-30 is made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system providing :

(2) Based on 0.8-3.1% potential fuel economy improvement obtained by switching from higher viscosity oils to a 5W-30 grade (M111 test-ACEA A3/B4). Actual savings are dependent upon vehicle/engine type, ambient weather, driving conditions and your current engine oil viscosity.

- Engine wear protection and lubrication over the full oil drain interval.
- Excellent protection for your engine by helping to prevent the buildup of harmful deposits
- Improved protection against variable fuel quality (1)
- Provides up to 1.5% fuel economy improvement (2)
- Provides outstanding high temperature protection over the entire oil drain interval

### Applications

Mobil 1 FS 5W-30 is recommended for many types of European vehicles.

- To be used for high performance engines in Volkswagen, Audi, Skoda, Mercedes Benz and other cars requiring the specifications and approvals listed below

### Specifications and Approvals

<b>This product has the following approvals:</b>
MB-Approval 229.3
MB-Approval 229.5
VW502 00
VW505 00
AVTOVAZ (LADA cars) Approved

<b>This product meets or exceeds the requirements of:</b>
APISN Engine Test Requirements
ACEA A3/B4

**This product meets or exceeds the requirements of:**

ACEA A3/B3

AAE (STO 003)Group B7

## Properties and Specifications

Property	
Grade	SAE 5W-30
Density @ 15 C, g/cm <sup>3</sup> , ASTM D4052	0.849
Flash Point, °C, ASTM D92	245
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	69.6
Pour Point, °C, ASTM D97	-42

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Mobil Oil Lubricants LLC : 123242, Moscow, Novinsky boulevard, 31, Russia

+ 7 (095) 232 22 23

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.ru/ru-ru/contact-us-technical>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved