

## TEBOIL MOTO K/T

### PRODUCT DESCRIPTION

High-quality mineral oil for saw chains.

### APPLICATIONS AND BENEFITS

- Designed for chain saws, forestry machinery units and other multi-profile equipment.
- Available in two versions: for winter (T) and for summer (K) operating conditions.
- Provides excellent adhesive properties, thereby reducing splashing and oil consumption during saw operation.

### TYPICAL TEST DATA

	MOTO T	MOTO K	Value	Test method
Density at 20 °C	878	887	kg/m <sup>3</sup>	ASTM D 4052
Kinematic viscosity at 40 °C	45	122	mm <sup>2</sup> /s	ASTM D 445
Kinematic viscosity at 100 °C	6,5	12,5	mm <sup>2</sup> /s	ASTM D 445
Viscosity index	90	90	-	ASTM D 2270
Flash point	180	180	°C	ASTM D 92
Pour point	-33	-18	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package.  
STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

