


MOL Hykomol 90

automotive gear oil



MOL Hykomol 90 is a monograde gear oil composed of highly refined base oils using additives having combined effects.

Application



Manual and automatic mechanical gearboxes of commercial vehicles

Manual gearboxes of passenger cars and light commercial vehicles

Oil lubricated rolling bearings

Manual gearboxes, gear drives of agricultural and construction machines

Features and benefits

Excellent wear protection

Up-to-date additive system

Low foaming tendency

Good thermal and oxidation stability

Outstanding corrosion protection

Long gear lifetime, giving reliable operation

Efficient EP performance, giving a long life for synchronizing rings

Stable, continuous lubricating film, giving reduced wear

Excellent properties are sustained for a long time

Long-term protection of parts

Specifications and approvals

Viscosity grade: SAE 90
API GL-4
MIL-L-2105

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,894
Kinematic viscosity at 40°C [mm ² /s]	165
Kinematic viscosity at 100 °C [mm ² /s]	15,4
Viscosity index	94
Pour point [°C]	-24
Flash point (Cleveland) [°C]	240

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Hykomol 90

automotive gear oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101987

SAP code and packaging:

13011265	MOL Hykomol 90 4L	4 l plastic can (for order only)
13010099	MOL Hykomol 90 10LA	10 l plastic can (for order only)
13006881	MOL Hykomol 90 180KG	216.5 l steel drum
13007870	MOL Hykomol 90	Road tank car (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.