


MOL Hykomol Arctic 75W-90

synthetic automotive gear oil



MOL Hykomol Arctic 75W-90 is a multigrade gear oil produced from premium quality synthetic base oils, using a state-of-art complex additive system. It ensures reliable lubrication even in extremely cold conditions.

Application



Manual and automatic mechanical gearboxes of commercial vehicles

Manual gearboxes in modern passenger cars, SUVs and light commercial vehicles

Features and benefits

Excellent cold flow properties

High viscosity index

Excellent shear stability

Outstanding oxidation stability

Excellent thermal stability

Excellent wear protection

Fuel-saving operation at low temperature

Optimum lubrication and reliable operation in a wide range of environmental and operational temperatures

Maintains its favourable properties for a long period even under heavy loads and shear stresses

Enables long drain interval application

Prevents formation of sludge and deposits, so servicing needs are reduced

Long gear lifetime, giving reliable operation

Specifications and approvals

Viscosity grade: SAE 75W-90
API GL-4

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,846
Kinematic viscosity at 40°C [mm ² /s]	100
Kinematic viscosity at 100 °C [mm ² /s]	16,0
Viscosity index	172
Pour point [°C]	-51
Flash point (Cleveland) [°C]	215

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Hykomol Arctic 75W-90

synthetic automotive gear oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 34031980

SAP code and packaging:

13301336 MOL Hykomol Arctic 75W-90 170KG

216.5 l steel drum (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.