

MOL Botond 20W-50

multigrade motor oil



MOL Botond 20W-50 it is engine oil produced from mineral base oils and a balanced additive system, for use in four-stroke petrol engines of earlier design.

Application



Gasoline and naturally aspirated diesel engines in passenger cars and light commercial vehicles of older construction

Vehicles with high mileage and high oil consumption

Features and benefits

High operational viscosity

Reduces oil consumption and improves internal sealing of the engine

Good lubricating film strength

Stable load-carrying lubricating film even in heavily worn, older engines

Multigrade engine oil

Suitable for use in the summer and winter, throughout the year

Good oxidation stability

Deposit formation at high temperatures is decreased
Cleaner engine

Specifications and approvals

Viscosity grade: SAE 20W-50
API SF/CC
MIL-L-46152B

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,887
Kinematic viscosity at 40°C [mm ² /s]	161,5
Kinematic viscosity at 100 °C [mm ² /s]	17,5
Viscosity index	118
Pour point [°C]	-24
Pourpoint [°C]	-27
Flash point (Cleveland) [°C]	240
Base number (BN) [mg KOH/g]	5,1

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

MOL Botond 20W-50

multigrade motor oil



Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13006055	MOL Botond 20W-50 X1L	1 l plastic bottle
13011113	MOL Botond 20W-50 4L	4 l plastic can
13006057	MOL Botond 20W-50 50KG	60 l steel drum

Order booking:

Please contact your local distributor or sales partner for ordering details.