# **EVOX Extra Ready -35**

# coolant, ready to use



EVOX Extra Ready -35 is a ready to use monoethylene-glycol based antifreeze coolant concentrate, produced with an OAT silicate hybrid additive system. It is free from nitrites, amines, phosphates, and is suitable for filling the cooling systems of internal combustion engines. EVOX Extra Ready -35 can be mixed with other monoethylene-glycol and monopropylene-glycol based antifreeze coolants without limitation.

## Application



Cooling sytems of passenger and commercial vehicles, agricultural and construction machines and stationary gas engines

Cooling systems containing cast iron, aluminium and copper parts

#### Features and benefits

Good corrosion protection

Application specific composition

Compatible with construction materials

#### **Specifications and approvals**

Forms a stable protective film on the inner surface of the cooling system to ensure a long lifetime

Protection against cavitation and sludge sedimentation

There's no damage to the plastic and rubber parts of the cooling system

BS 6580:2010 ASTM D 3306 ASTM D 4985 AFNOR R-15-601 VW/Audi/Seat/Skoda TL 774-C (VW code G11) Ford ESD-M97B49-A MAN 324 Typ NF MTU MTL 5048 Cummins 85T8-2 Opel-GM GME L1301 Volvo Construction 128 6083/002 Volvo Trucks 128 6083/002

# **EVOX Extra Ready -35**

coolant, ready to use



### **Properties**

Properties	Typical values
Appearance	blue
Density at 15°C [g/cm3]	1,079
pH value	8,4
Freezing point [°C]	-38
Alkalinity [ml 0,1M HCl/10 ml]	8,4
Boiling point [°C]	105
Refractive index at 20 °C	1,3867

The characteristics in table are typical values of the product and do not constitute a specification.

## Storage and handling instructions

Should be stored in its original packaging with airproof sealing, separately from foods, in a place protected against water and sunshine, locked away from children. In the original container under the recommended storage conditions: 48 months Recommended storage temperature:  $-35^{\circ}C - +30^{\circ}C$ 

4 I plastic can

IBC (for order only)

216.5 | steel drum (for order only)

### **Ordering information**

Custom Tariff Number 38200000

#### SAP code and packaging:

 19002770
 EVOX Extra Ready -35 4L

 19002771
 EVOX Extra Ready -35 220KG

 19002773
 EVOX Extra Ready -35 1100KG

#### Order booking:

Please contact your local distributor or sales partner for ordering details.