

# MARTOL EV 45



*Metalworking*



**Pressing oil evanescent fluid.**

## UTILISATIONS

- Evanescent extreme-pressure fluid for difficult operations on all metals.
- Cutting, pressing, punching.
- Application: felt pad, brush, drop by drop, rollers.
- Optimum results are obtained by using low-pressure sprayers.

## ADVANTAGES

- Excellent spreading of oil film.
- Good wettability.
- Do not store at temperatures below 10°C. Otherwise, before use store for at least 24 hours at ambient working temperature. Use a pump to agitate product in order to ensure homogeneous remixing.
- Leaves a greasy residue which gives the remaining film anticorrosion protection properties.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL EV 45
Film aspect	Visual	-	dry
Covering ability	ASTM D 591160	m <sup>2</sup> /kg	414
Specific gravity at 15 °C	ASTM D 1298	kg/m <sup>3</sup>	0.858
Kinematic viscosity at 20°C	ASTM D 445	mm <sup>2</sup> /s	2.2
Kinematic viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	1.58
Flash point O.C.	ASTM D 92	°C	51
Flash point C.C. (Abel-Pensky)	ISO 1523	°C	40

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS**  
**Industrie & Spécialités**

6 septembre 2001

MARTOL EV 45

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser [www.quick-fds.com](http://www.quick-fds.com).

