

# MOL ATF 295

## synthetic automatic transmission fluid



MOL ATF 295 is a premium quality automatic transmission fluid produced from high performance fully synthetic base oils, using an additive system that meets the highest quality requirements. Its use is particularly recommended in Allison and ZF transmission gears with extra long oil change intervals.

### Application



Automatic transmissions in modern commercial vehicles

### Features and benefits

Improved wear protection

Wear is kept to a minimum, even in gears exposed to increased loads  
Reliable equipment protection and long machine lifetime

Exceptional thermal and oxidation stability

Longer lubricant lifetime, so reduced operational costs

Optimal friction characteristics

Precise and noiseless switching between gears  
Convenient and economical operation

Excellent shear stability

Preserves its rheological properties even under severe operating conditions and high temperatures

High viscosity index

Optimum lubrication and reliable operation in a wide range of environmental and operational temperatures

Excellent cold flow properties

Fuel-saving operation at low temperature

### Specifications and approvals

ZF TE-ML 16S[ZF003361]  
ZF TE-ML 20C[ZF003361]  
ZF TE-ML 25C[ZF003361]  
Voith H55.6336  
MAN 339 Typ V2  
MAN 339 Typ Z12  
MAN 339 Typ Z3  
ZF TE-ML 02F  
ZF TE-ML 03D  
ZF TE-ML 04D  
ZF TE-ML 14C  
ZF TE-ML 16M  
ZF TE-ML 17C  
Allison C-4  
Allison TES-295  
Allison TES-389

# MOL ATF 295

## synthetic automatic transmission fluid



### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,849
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	38,0
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	7,4
Viscosity index	165
Pour point [°C]	-51
Flash point (Cleveland) [°C]	245

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 34031980

#### SAP code and packaging:

13009032 MOL ATF 295 47KG

60 l steel drum (for order only)

13009031 MOL ATF 295 170KG

216.5 l steel drum (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.