





RAVENOL SNOWMOBILES 4-Takt Fullsynth.



ART.-NR. 1151311

1L | 1151311-001 4 L | 1151311-004 10 L | 1151311-010 20 L | 1151311-020 20 L | 1151311-B20 1000 L | 1151311-700 SPECIFICATIONS API SN
FABRICATION FULLY SYNTHETIC
RECOMMENDATIONS BOMBARDIER | ARCTIC CAT | KAWASAKI | SKIDOO | POLARIS | YAMAHA | SUZUKI

RAVENOL SNOWMOBILES 4-Takt Fullsynth. is a fully synthetic high quality green coloured engine oil based on PAO (Polyalphaolefin).

Due to its special additives and a special formulation **RAVENOL SNOWMOBILES 4-Takt Fullsynth.** achieves an extremely high viscosity stability. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

By significantly reducing fuel consumption, **RAVENOL SNOWMOBILES 4-Takt Fullsynth.** helps to protect the environment by reducing emissions.

Application Notes

RAVENOL Snowmobiles 4-Stroke Fullsynth. is a fuel-efficient engine oil specifically developed for use in 4 -Stroke Snowmobile engines.

Characteristics

RAVENOL Snowmobiles 4-Takt Fullsynth. offers:

- Fast lubrication of the engine, even at temperatures below -35 ° C.
- Low tendency to evaporate, thereby lower oil consumption.
- Enhanced protection against carbon deposits and varnish even in the most unfavorable conditions.
- No oil-related deposits in combustion chambers in the piston ring zone and on valves.
- Unchanged viscosity throughout the oil change interval, high viscosity index.
- Compatible with all types of sealing materials.

Property	Unit	Data	Audit
Density at 20°C	kg/m³	843	EN ISO 12185
Colour		grün	visual
Viscosity at 100°C	mm²/s	12,2	DIN 51 562

- Certificate / Product Information -





Property	Unit	Data	Audit
Dissosity/tyata24000	krg/m²/s	69,2	DIN 517562
Viscosity index VI		176	DIN ISO 2909
CCS Viscosity at -35°C	mPa*s	5610	ASTM D5293
Pourpoint	°C	-51	DIN ISO 3016
Flash point (COC)	°C	236	DIN ISO 2592
TBN	mg KOH/g	10,0	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019