

# MOL Dynamic Forest

## chain-saw lubricating oil



MOL Dynamic Forest is a high quality chain lubricating oil containing additives that prevent scuffing and improve adhesion, inhibit oxidation and corrosion, developed for state-of-art chain saws.

### Application



Hand chainsaws used for logging

### Features and benefits

Excellent wear protection

Wear of chain elements, teeth and the guide bar are reduced  
Long chain lifetime

Excellent adhesion, strong tackiness

Enables economical use

Excellent cold flow properties

Suitable for logging throughout the year

### Specifications and approvals

Viscosity grade: ISO VG 100

### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,888
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	100
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	10,9
Viscosity index	92
Pour point [°C]	-27
Flash point (Cleveland) [°C]	260

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

# MOL Dynamic Forest

## chain-saw lubricating oil



### Ordering information

Custom Tariff Number 27101999

#### SAP code and packaging:

13006089	MOL Dynamic Forest X0,6L	0,6 l plastic bottle
13006091	MOL Dynamic Forest X1L	1 l plastic bottle
13006092	MOL Dynamic Forest X4L	4 l plastic can
13006090	MOL Dynamic Forest 180KG	216.5 l steel drum

#### Order booking:

Please contact your local distributor or sales partner for ordering details.